

# Granite<sup>®</sup> Standard

guarantee **10** years  
free of chromates and heavy metals

<b>Properties</b>	<ul style="list-style-type: none"> <li>• Good corrosion resistance</li> <li>• Good formability</li> <li>• Thermosetting paint</li> <li>• Surface treatment and paint: free of hexavalent chromium and heavy metals</li> </ul>																																								
<b>Applications</b>	<b>Basic coating for outdoor applications (cladding, roofing and accessories, air conditioners)</b>																																								
<b>Description</b>	<table border="1"> <tr> <td>Thickness <sup>(1)</sup></td> <td>25 microns</td> </tr> <tr> <td>Composition</td> <td>Front: 5 microns primer + 20 microns top coat Back: 5, 7, 10 or 12 microns backing coat Double-side finish available</td> </tr> <tr> <td>Gloss (Gardner 60°) <sup>(1)</sup></td> <td>30 GU Other gloss levels on request</td> </tr> <tr> <td>Colours</td> <td>Colour palette Other colours on request</td> </tr> <tr> <td>Appearance</td> <td>Smooth</td> </tr> <tr> <td>Temporary protection (optional)</td> <td>Self-adhesive film or heat-sealed film</td> </tr> </table>	Thickness <sup>(1)</sup>	25 microns	Composition	Front: 5 microns primer + 20 microns top coat Back: 5, 7, 10 or 12 microns backing coat Double-side finish available	Gloss (Gardner 60°) <sup>(1)</sup>	30 GU Other gloss levels on request	Colours	Colour palette Other colours on request	Appearance	Smooth	Temporary protection (optional)	Self-adhesive film or heat-sealed film																												
Thickness <sup>(1)</sup>	25 microns																																								
Composition	Front: 5 microns primer + 20 microns top coat Back: 5, 7, 10 or 12 microns backing coat Double-side finish available																																								
Gloss (Gardner 60°) <sup>(1)</sup>	30 GU Other gloss levels on request																																								
Colours	Colour palette Other colours on request																																								
Appearance	Smooth																																								
Temporary protection (optional)	Self-adhesive film or heat-sealed film																																								
<b>Performance</b>	<table border="1"> <tr> <td>Adhesion of the coating (T-bend)</td> <td>≤ 2 T</td> </tr> <tr> <td>Resistance to cracking on bending (T-bend)</td> <td>≤ 3 T</td> </tr> <tr> <td>Impact resistance</td> <td>18 J</td> </tr> <tr> <td>Surface "pencil" hardness</td> <td>HB to H</td> </tr> <tr> <td>Clemen scratch resistance</td> <td>≥ 2 kg</td> </tr> <tr> <td>Corrosion resistance:</td> <td></td> </tr> <tr> <td>• Salt spray test</td> <td>360 hours</td> </tr> <tr> <td>• Corrosion resistance category</td> <td>RC3</td> </tr> <tr> <td>Condensation resistance (QCT)</td> <td>1000 hours</td> </tr> <tr> <td>UV resistance:</td> <td></td> </tr> <tr> <td>• QUV (UVA + H<sub>2</sub>O) test (2000 hours)</td> <td>ΔE ≤ 5; GR ≥ 30%</td> </tr> <tr> <td>• UV resistance category</td> <td>RUV2</td> </tr> <tr> <td>Fire behaviour classification (EN 13501-1)</td> <td>A1</td> </tr> <tr> <td>Resistance to acids and bases</td> <td>Good</td> </tr> <tr> <td>Resistance to solvents:</td> <td></td> </tr> <tr> <td>• Aliphatics and alcohols</td> <td>Very good</td> </tr> <tr> <td>• Ketones</td> <td>Low</td> </tr> <tr> <td>• Aromatics</td> <td>Good to very good</td> </tr> <tr> <td>Resistance to mineral oils</td> <td>Very good</td> </tr> <tr> <td>Maximum continuous operating temperature</td> <td>100°C</td> </tr> </table>	Adhesion of the coating (T-bend)	≤ 2 T	Resistance to cracking on bending (T-bend)	≤ 3 T	Impact resistance	18 J	Surface "pencil" hardness	HB to H	Clemen scratch resistance	≥ 2 kg	Corrosion resistance:		• Salt spray test	360 hours	• Corrosion resistance category	RC3	Condensation resistance (QCT)	1000 hours	UV resistance:		• QUV (UVA + H <sub>2</sub> O) test (2000 hours)	ΔE ≤ 5; GR ≥ 30%	• UV resistance category	RUV2	Fire behaviour classification (EN 13501-1)	A1	Resistance to acids and bases	Good	Resistance to solvents:		• Aliphatics and alcohols	Very good	• Ketones	Low	• Aromatics	Good to very good	Resistance to mineral oils	Very good	Maximum continuous operating temperature	100°C
Adhesion of the coating (T-bend)	≤ 2 T																																								
Resistance to cracking on bending (T-bend)	≤ 3 T																																								
Impact resistance	18 J																																								
Surface "pencil" hardness	HB to H																																								
Clemen scratch resistance	≥ 2 kg																																								
Corrosion resistance:																																									
• Salt spray test	360 hours																																								
• Corrosion resistance category	RC3																																								
Condensation resistance (QCT)	1000 hours																																								
UV resistance:																																									
• QUV (UVA + H <sub>2</sub> O) test (2000 hours)	ΔE ≤ 5; GR ≥ 30%																																								
• UV resistance category	RUV2																																								
Fire behaviour classification (EN 13501-1)	A1																																								
Resistance to acids and bases	Good																																								
Resistance to solvents:																																									
• Aliphatics and alcohols	Very good																																								
• Ketones	Low																																								
• Aromatics	Good to very good																																								
Resistance to mineral oils	Very good																																								
Maximum continuous operating temperature	100°C																																								
<b>Automatic guarantee</b>	<ul style="list-style-type: none"> <li>• Non-perforation of the sheet metal ≤ 10 years, depending on the external environment</li> <li>• Non-delamination of the paint ≤ 10 years, depending on the external environment</li> <li>• Aesthetic appearance (ΔE ≤ 5; Gloss retention ≥ 30%) ≤ 5 years, depending on the geographic location and the paint colour category</li> </ul>																																								
<b>Remarks</b>	<p>These performance characteristics refer specifically to metallic coating z275 and Optigal<sup>®</sup> zM120 (guaranteed minimum). If any product (film, oil, foam, glue, paint etc) is to be applied after coil delivery, compatibility with the coating needs to be checked first. Although we take great care to reproduce the same aesthetic aspect on each coil, ArcelorMittal cannot guarantee the visual consistency from one single order item to another. Consequently, you need to consider placing one single order for one building; standard samples can only serve as a guide.</p>																																								

(1) Nominal value, tolerance according to EN 10169